



# SUPERIOR INTERLOCK CORPORATION

73-39 CENTRAL AVENUE  
 GLENDALE, NY 11385  
 (718) 821-8949 fax (718) 417-6162  
 www.superiorinterlock.com



## INTERLOCK DATA SHEET FOR SUPERIOR-CORY KEY INTERLOCKS

date: \_\_\_ / \_\_\_ /200\_\_

cust#: \_\_\_ - \_\_\_\_\_  
 cust: \_\_\_\_\_ ship to: \_\_\_\_\_ ultimate user #: \_\_\_\_\_  
 address: \_\_\_\_\_ name: \_\_\_\_\_  
 city: \_\_\_\_\_ state: \_\_\_\_\_  
 zip: \_\_\_\_\_ country: \_\_\_\_\_ location: \_\_\_\_\_  
 purchasing: \_\_\_\_\_ state: \_\_\_\_\_ city: \_\_\_\_\_  
 P.O.#: \_\_\_\_\_ zip: \_\_\_\_\_ country: \_\_\_\_\_ state: \_\_\_\_\_  
 tel: \_\_\_\_\_ marks: \_\_\_\_\_ country: \_\_\_\_\_  
 fax: \_\_\_\_\_

ITEM	QTY	CATALOG NO.	TYPE NO.	BOLT EXT	E/W	INTER	KEY#	COVER	ACC	MH	O.H.	COIL VOLTAGE	REMARKS:
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													
14													
15													
16													
17													
18													
19													
20													

NOTE: BOLT EXTENSION TO BE SPECIFIED IN THE LOCKING BOLT WITHDRAWN POSITION. TRAVEL IS MECHANICALLY FIXED AT 3/4"  
 O.H. = OPPOSITE HAND = LOCKING BOLT POINTS TO RIGHT. COVER Y/N YES SPEC DC1 OR DC2 N= NO COVER ACC=ACCESSORIES. MH=MOUNTING HARDWARE  
 SOLENOID KEY RELEASE UNITS PLEASE SPECIFY REQUIRED "COIL VOLTAGE" SOL1=120vac SOL2=24vdc SOL3=125vdc SOL4=48vdc SOL5=240 Vac SOL6=250vdc

SPECIAL NOTES: