



TYPE B-1088 KEY TRANSFER INTERLOCK TECHNICAL INFORMATION

| CAT # INDOOR | SHIP WT. | CAT # OUTDOOR | SHIP WT. | TOP CYL | BOT CYL | BLANK | ENCL SIZE |
|--------------|----------|---------------|----------|---------|---------|-------|-----------|
| S105658Y | 1.6 | S105658YOD | 3.2 | 1 | 1 | 1 | 3K |
| S105659Y | 1.8 | S105659YOD | 3.4 | 2 | 1 | 0 | 3K |
| S105660Y | 2.9 | S105660YOD | 5.3 | 3 | 1 | 2 | 6K |
| S105661Y | 2.9 | S105661YOD | 5.3 | 2 | 2 | 2 | 6K |
| S105662Y | 3.2 | S105662YOD | 5.5 | 4 | 1 | 1 | 6K |
| S105663Y | 3.2 | S105663YOD | 5.5 | 3 | 2 | 1 | 6K |
| S105664Y | 3.4 | S105664YOD | 5.8 | 5 | 1 | 0 | 6K |
| S105665Y | 3.4 | S105665YOD | 5.8 | 4 | 2 | 0 | 6K |
| S105666Y | 3.4 | S105666YOD | 5.8 | 3 | 3 | 0 | 6K |
| S105667Y | 4.7 | S105667YOD | 8.0 | 6 | 1 | 2 | 9K |
| S105668Y | 4.7 | S105668YOD | 8.0 | 5 | 2 | 2 | 9K |
| S105669Y | 4.7 | S105669YOD | 8.0 | 4 | 3 | 2 | 9K |
| S105670Y | 5.0 | S105670YOD | 8.2 | 7 | 1 | 1 | 9K |
| S105671Y | 5.0 | S105671YOD | 8.2 | 6 | 2 | 1 | 9K |
| S105672Y | 5.0 | S105672YOD | 8.2 | 5 | 3 | 1 | 9K |
| S105673Y | 5.0 | S105673YOD | 8.2 | 4 | 4 | 1 | 9K |
| S105674Y | 5.2 | S105674YOD | 8.4 | 8 | 1 | 0 | 9K |
| S105675Y | 5.2 | S105675YOD | 8.4 | 7 | 2 | 0 | 9K |
| S105676Y | 5.2 | S105676YOD | 8.4 | 6 | 3 | 0 | 9K |
| S105677Y | 5.2 | S105677YOD | 8.4 | 5 | 4 | 0 | 9K |
| S105678Y | 6.2 | S105678YOD | 10.7 | 9 | 1 | 2 | 12K |
| S105679Y | 6.2 | S105679YOD | 10.7 | 8 | 2 | 2 | 12K |
| S105680Y | 6.2 | S105680YOD | 10.7 | 7 | 3 | 2 | 12K |
| S105681Y | 6.2 | S105681YOD | 10.7 | 6 | 4 | 2 | 12K |
| S105682Y | 6.2 | S105682YOD | 10.7 | 5 | 5 | 2 | 12K |
| S105683Y | 6.4 | S105683YOD | 11.0 | 10 | 1 | 1 | 12K |
| S105684Y | 6.4 | S105684YOD | 11.0 | 9 | 2 | 1 | 12K |
| S105685Y | 6.4 | S105685YOD | 11.0 | 8 | 3 | 1 | 12K |
| S105686Y | 6.4 | S105686YOD | 11.0 | 7 | 4 | 1 | 12K |
| S105687Y | 6.4 | S105687YOD | 11.0 | 6 | 5 | 1 | 12K |
| S105688Y | 6.6 | S105688YOD | 11.2 | 11 | 1 | 0 | 12K |
| S105689Y | 6.6 | S105689YOD | 11.2 | 10 | 2 | 0 | 12K |
| S105690Y | 6.6 | S105690YOD | 11.2 | 9 | 3 | 0 | 12K |
| S105691Y | 6.6 | S105691YOD | 11.2 | 8 | 4 | 0 | 12K |
| S105692Y | 6.6 | S105692YOD | 11.2 | 7 | 5 | 0 | 12K |
| S105693Y | 6.6 | S105693YOD | 11.2 | 6 | 6 | 0 | 12K |

OUTDOOR STORM SHED ENCLOSED UNIT

| ENCL | 3K | 6K | 9K | 12K |
|-------|-------|--------|--------|--------|
| DIM A | 7" | 11.88" | 16.75" | 21.56" |
| DIM B | 7.75" | 12.62" | 17.5" | 22.31" |
| DIM C | 8.4 | 13.2" | 18.1" | 23" |

3K = 3 KEY HOUSING 2 TO 3 CYLINDERS
 6K = 6 KEY HOUSING 4 TO 6 CYLINDERS
 9K = 9 KEY HOUSING 7 TO 9 CYLINDERS
 12K = 12 KEY HOUSING 10 TO 12 CYLINDERS

GENERAL SPECS
 CASE & STORM SHED: CAST ALUMINUM
 COVER PLATE: STAINLESS STEEL
 LOCK CYLINDER: BRASS
 INTERNAL LINKAGE: BRASS
 HARDWARE: STAINLESS STEEL
 FINISH: BRIGHT ALUMINUM PAINT
 CALL FACTORY FOR DETAILS

AVAILABLE ACCESSORIES

| | | | |
|--------------|-----------|-----|--------|
| ○ SLP | CMTR | ○ ○ | ⊕ ⊖ |
| ○ FUTURE CYL | MAX 9 CYL | ○ ○ | DUAL ⊕ |
| ○ / ⊕ KC | ⊕ ⊕ MH | ⊕ | ⊕ ACYL |

SUPERIOR INTERLOCK CORP
 73-39 CENTRAL AVENUE
 GLENDALE, NY 11385
 TEL (718) 821-8949
 FAX (718) 417-6162
 www.superiorinterlock.com

